



TNCrev. plug (m) - TNC plug (m)

Order-No.	Type	Connector left	Connector right	Cable	Cable length	Attenuation
52010174	R-AC 3 TNC-TNCR	TNC plug (m)	TNCrev. plug (m)	LL 240 flex	3 m	1 dB
52010175	R-AC 6 TNC-TNCR	TNC plug (m)	TNCrev. plug (m)	LL 240 flex	6 m	2 dB
52010176	R-AC 10 TNC-TNCR	TNC plug (m)	TNCrev. plug (m)	LL 240 flex	10 m	3.3 dB
52010177	R-AC 15 TNC-TNCR	TNC plug (m)	TNCrev. plug (m)	LL 240 flex	15 m	5 dB
52010090	R-AC 3 SMA-TNCR	SMA plug (m)	TNCrev. plug (m)	RG 58	3 m	1.5 dB
52010208	R-AC 05 SMA-SMA	SMA plug (m)	SMA plug (m)	RG 58	0.5 m	0.5 dB

Technical data cable LL 240 flex:

- Cable type LowLoss 240 flex
- Impedance 50 Ohm
- Screening effectiveness >90 dB
- Jacket PE, black
- Diameter 5.4 ± 0.2 mm
- Minimum bend radius 35 mm (single bend)
- Operating temperature range -40°C to +80°C
- Degree of protection IP 65 (if screwed)


Technical data cable RG 58:

- Cable type RG 58
- Impedance 50 Ohm
- Jacket PE, black
- Diameter 4.95 ± 0.2 mm
- Minimum bend radius 35 mm (single bend)
- Operating temperature range -40°C to +80°C

Order-No.	Type	connector left	connector right	Technical data	degree of protection
52010178	R-AA TNC-N (f-m)	TNC socket (f)	N plug (m)	for the connection of WiRa antennas, Order-No.: 52010086, 52010087	IP 65 (if screwed)
52010243	R-AA TNC-SMA (f-m)	TNC socket (f)	SMA plug (m)	for the connection of SMSH antenna, Order-No.: 52010197	



Adaptor 52010178



Adaptor 52010243



TNCrev. Stecker - TNC Stecker

Bestell-Nr.	Typ	Anschluss links	Anschluss rechts	Kabel	Kabellänge	Dämpfung
52010174	R-AC 3 TNC-TNCR	TNC Stecker	TNCrev. Stecker	LL 240 flex	3 m	1 dB
52010175	R-AC 6 TNC-TNCR	TNC Stecker	TNCrev. Stecker	LL 240 flex	6 m	2 dB
52010176	R-AC 10 TNC-TNCR	TNC Stecker	TNCrev. Stecker	LL 240 flex	10 m	3,3 dB
52010177	R-AC 15 TNC-TNCR	TNC Stecker	TNCrev. Stecker	LL 240 flex	15 m	5 dB
52010090	R-AC 3 SMA-TNCR	SMA Stecker	TNCrev. Stecker	RG 58	3 m	1,5 dB
52010208	R-AC 05 SMA-SMA	SMA Stecker	SMA Stecker	RG 58	0,5 m	0,5 dB

Technische Ausstattung Kabel LL 240 flex:

- Kabeltyp LowLoss 240 flex
- Impedanz 50 Ω
- Schirmdämpfung >90 dB
- Außenmantel PE, schwarz
- Durchmesser 5,4 $\pm$ 0,2 mm
- Biegeradius 35 mm (einmalig)
- Betriebs-Temperaturbereich -40°C bis +80°C
- Schutzart IP 65 (im verschraubten Zustand)


Technische Ausstattung Kabel RG 58:

- Kabeltyp RG 58
- Impedanz 50 Ω
- Außenmantel PE, schwarz
- Durchmesser 4,95 $\pm$ 0,2 mm
- Biegeradius 35 mm (einmalig)
- Betriebs-Temperaturbereich -40°C bis +80°C

Bestell-Nr.	Typ	Anschluss links	Anschluss rechts	technische Ausstattung	Schutzart
52010178	R-AA TNC-N (f-m)	TNC-Buchse	N-Stecker	zum Anschluss der WiRa Antennen, Bestell-Nr.: 52010086, 52010087	IP 65
52010243	R-AA TNC-SMA (f-m)	TNC-Buchse	SMA-Stecker	zum Anschluss der SMSH Antenne, Bestell-Nr.: 52010197	(im verschraubten Zustand)



Adapter 52010178



Adapter 52010243